



FRONTIER 9.18
IS FORM
VER 1.0

FTR ISDN BRI/PRI Service (IS)

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
IS{							
IS_ADMIN{							
001	PON - Purchase Order Number	DO NOT MAP				NOT SUPPORTED BY FTR	
002	VER - Version Identification	DO NOT MAP				NOT SUPPORTED BY FTR	
003	AN - Account Number	DO NOT MAP				NOT SUPPORTED BY FTR	
004	ATN - Account Telephone Number	DO NOT MAP				NOT SUPPORTED BY FTR	
005	IQTY - ISDN Quantity		Numeric	1-5		1. If not populated, then return error: FTRIS001 IQTY IS REQUIRED 2. If populated and (dl > 5 or dc ≠ numeric), then return error: FTRIS002 IQTY VALID VALUE = 1-5 NUMERIC	R
006	ORD - Order Number	DO NOT MAP				NOT SUPPORTED BY FTR	
007	CB - Common Block	DO NOT MAP				NOT SUPPORTED BY FTR	
008	PG_of_ - Page_of_	DO NOT MAP				NOT SUPPORTED BY FTR	
009	DPG - Dialing Plan Group	DO NOT MAP				NOT SUPPORTED BY FTR	
}							
IS_SVC_DET{							
010	LOCNUM - Location Number		Numeric	1-3		1. If not populated, then return error: FTRIS008 LOCNUM IS REQUIRED 2. If populated and (dl > 3 or dc ≠ numeric), then return error: FTRIS009 LOCNUM VALID VALUE = 1-3 NUMERIC	R
011	LNUM - Line Number		Numeric	1-5		1. If not populated, then return error:	R

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						FTRIS010 LNUM IS REQUIRED 2. If populated and (dl > 5 or dc ≠ numeric), then return error: FTRIS011 LNUM VALID VALUE = 1-5 NUMERIC	
012	LNEX	DO NOT MAP				NOT SUPPORTED BY FTR	
013	NPI – Number Portability Indicator		Alpha	1	C, E, F	1. If populated and vv is not C, E, F return error message FTRIS003 NPI VALID VALUES ARE C, E OR F 2. If not populated and LSR.NPDI is B, D return error message FTRIS004 NPI IS REQUIRED WHEN NPDI IS B OR D 3. If populated and LSR.NPDI is not B, D return error message FTRIS005 NPI IS NOT ALLOWED WHEN NPDI IS NOT B OR D	O
014	LNA - Line Activity		Alpha	1-1	C = Change, e.g., rearrangement, feature activity N = New installation and/or account P = PIC change V = Conversion or migration of service as specified W = Migration as is X = Telephone number change D = Disconnect	1. If not populated, then return error: FTRIS015 LNA IS REQUIRED 2. If populated and vv ≠ C, D, N, V, W, X, P, then return error: FTRIS016 LNA VALID VALUE = C, D, N, V, W, X, P 3. If populated and vv is V and LSR.ACT is C return error message FTRIS006 LNA MAY NOT BE V IF LSR ACT IS C 4. If populated and vv is not N and LSR.ACT is N return error message FTRIS007 LNA MUST BE N WHEN LSR ACT IS N	R

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						5. If populated and vv is not V, N, D and LSR.ACT is V return error message FTRIS012 LNA MUST BE V, N OR D WHEN LSR ACT IS V	
015	LTOS - Line Type of Service	DO NOT MAP				NOT SUPPORTED BY FTR	
015a	DIDNBR – DID Number		N	5	1-10000	1. If populated and (dl > 5 or vv ≠ 1-10000), then return error: FTRIS260 DIDNBR VALID VALUE = 1 – 10000 2. If not populated and character position 2 of LSR.TOS = K, then return error: FTRIS261 DIDNBR REQUIRED WHEN CHARACTER 2 OF TOS = K	
016	SOE - Service or Equipment Indicator	DO NOT MAP				NOT SUPPORTED BY FTR	
017	NOTYP - Number Type		Alpha	1-1	A, B, C	1. If not populated and (TNS or OTN is populated), then return error: FTRIS025 NOTYP IS REQUIRED 2. If populated and (TNS and OTN are not populated), then return error: FTRIS026 NOTYP IS PROHIBITED 3. If populated and vv ≠ A, B, C then return error: FTRIS027 NOTYP VALID VALUE = A, B OR C	O
018	TNS - Telephone		Alphanumeric	1-15, N		1. If not populated, then return error:	R

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
	Numbers					FTRIS028 TNS IS REQUIRED 2. If populated and dl > 15, then return error: FTRIS029 TNS VALID LENGTH = 1-15 3. If populated and dc is 1 alpha and vv is not N return error message FTRIS217 TNS MUST BE N IF IT IS ONE ALPHA CHARACTER	
019	PN - Primary Number	DO NOT MAP				NOT SUPPORTED BY FTR	
020	DTN - Data Telephone Number	DO NOT MAP				NOT SUPPORTED BY FTR	
021	S - Suspend Activity Indicator	DO NOT MAP				NOT SUPPORTED BY FTR	
022	SPLD - State Primary Line Designator	DO NOT MAP				NOT SUPPORTED BY FTR	
023	OTN - Out Telephone Number		Numeric	10-10		1. If not populated and LNA = X then return error: FTRIS037 OTN IS REQUIRED 2. If populated and (dl ≠ 10 or dc ≠ numeric), then return error: FTRIS038 OTN VALID VALUE = 10 NUMERIC	O
024	DOTN - Data Out Telephone Number	DO NOT MAP				NOT SUPPORTED BY FTR	O
025	TERS - Terminal Numbers		Alphanumeric	1-10		1. If populated and dl > 10, then return error: FTRIS043 TERS VALID LENGTH = 1-10	O
026	TSP - Telecommunications Service Priority		Alphanumeric	12-12	Format = XXXXXXXXXX-XN N = Numeric X = Alpha/Numeric	1. If populated and format ≠ XXXXXXXXXX-XN, then return error: FTRIS044 TSP VALID FORMAT = XXXXXXXXXX-XN	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						<p>2. If populated and position 11 of vv ≠ E, 0, 1, 2, 3, 4, 5, then return error: FTRIS045 TSP VALID VALUE FOR POSITION 11 = E, 0, 1, 2, 3, 4, 5</p> <p>3. If populated and position 12 of vv ≠ 0, 1, 2, 3, 4, 5, then return error: FTRIS046 TSP VALID VALUE FOR POSITION 12 = 0, 1, 2, 3, 4, 5</p> <p>4. If populated and LNA is p, x return error message FTRIS041 TSP ISPROHIBITED WITH LNA OF P OR X</p> <p>5. If populated and character position 2 of LSR.TOS is 2 return error message FTRIS042 TSP IS NOT ALLOWED WITH THIS TOS</p>	
027	SAN - Subscriber Authorization Number		Alphanumeric	1-30		1. If populated and dl > 30, then return error: FTRIS047 SAN VALID LENGTH = 1-30	O
028	CKR - Customer Circuit Reference		Alphanumeric	1-41		1. If populated and dl > 41, then return error: FTRIS048 CKR VALID LENGTH = 1-41	O
029	ECCKT - Exchange Company Circuit ID		Alphanumeric , virgule	1-41		<p>1. If populated and dl > 41, then return error: FTRIS049 ECCKT MAY NOT EXCEED 41 CHARACTERS</p> <p>2. If populated and LNA is P, X return error message FTRIS218 ECCKT IS PROHIBITED WHEN LNA IS P OR X</p> <p>3. If populated and special characters are not virgules return error message</p>	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						FTRIS219 ECCKT SPECIAL CHARACTERS MAY ONLY BE VIRGULE (FORWARD SLASH) 4. If populated and data contains virgule and virgule is not immediately preceded and followed by a numeric return error message FTRIS220 VIRGULE MUST BE IMMEDIATELY PRECEDED AND FOLLOWED BY A NUMERIC	
030	RL - Reuse Loop		Alpha	1-1	Y	1. If populated and LNA ≠ V then return error: FTRIS050 RL IS PROHIBITED 2. If populated and vv ≠ Y, then return error: FTRIS051 RL VALID VALUE = Y	O
031	OECCKT - Out Exchange Company Circuit ID		Alphanumeric	1-41		1. If not populated and RL is populated then return error: FTRIS052 OECCKT IS REQUIRED 2. If populated and RL is not populated, then return error: FTRIS053 OECCKT IS PROHIBITED 3. If populated and dl > 41 then return error: FTRIS054 OECCKT MAY NOT EXCEED 41 CHARACTERS	O
032	FPI - Freeze PIC Indicator		Alpha	1-1	A, B, E, R, S, T	1. If populated and vv ≠ A, B, E, R, S, T, then return error: FTRIS055 FPI VALID VALUE = A, B, E, R, S, T	O
033	PIC - InterLATA Pre-subscription Indicator Code		Alphanumeric	2-4	Valid PIC Code NONE NC	1. If not populated and LNA = N, P, then return error: FTRIS056 PIC IS REQUIRED 2. If populated and vv ≠ NONE, NC and	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						((dl < 2 or > 4) or (dc ≠ numeric)), then return error: FTRIS057 PIC VALID VALUE = NONE, NC OR 2-4 NUMERIC	
034	LPIC - IntraLATA Pre-subscription Indicator Code		Alphanumeric	2-4	Valid PIC Code NONE NC	1. If not populated and LNA = N, P, then return error: FTRIS058 LPIC IS REQUIRED 2. If populated and vv ≠ NONE, NC and ((dl < 2 or > 4) or (dc ≠ numeric)), then return error: FTRIS059 LPIC VALID VALUE = NONE, NC OR 2-4 NUMERIC	O
035	IPIC - International Pre-subscription Indicator Code	DO NOT MAP				NOT SUPPORTED BY FTR	
036	SDI - Switched Data Identifier		Alpha	1-1	E, F, G, H, I, J, K, L, M	1. If populated and vv ≠ E, F, G, H, I, J, K, L, M, then return error: FTRIS061 SDI VALID VALUE = E, F, G, H, I, J, K, L, M	O
037	MATN - Main/Alternate Telephone Number		Alpha	1-1	A, M	1. If populated and position 2 of LSR.TOS ≠ H then return error: FTRIS062 MATN IS PROHIBITED 2. If populated and vv ≠ A, M, then return error: FTRIS063 MATN VALID VALUE = A, M	O
}							
TRANSFER OF CALLS							
038	TC_OPT - Transfer of Call Options		Alphanumeric	1-3	N, S, T	1. If populated and vv is not N, S, T, then return error: FTRIS064 TC OPT VALID VALUE = N, S, T	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
039	TC_TO_PRI - Transfer of Calls To Primary Number		Numeric	10-10		<p>1. If not populated and TC_OPT = T, then return error: FTRIS065 TC TO PRI IS REQUIRED</p> <p>2. If populated and (dl ≠ 10 or dc ≠ numeric), then return error: FTRIS066 TC TO PRI VALID VALUE = 10 NUMERIC</p> <p>3. If populated and TC OPT is not T return error message FTRIS221 TC TO PRI IS NOT ALLOWED IF TC OPT IS NOT T</p>	O
042	TCID - Transfer of Calls To Identifier		Numeric	1-2		<p>1. If not populated and TC_OPT = T, then return error: FTRIS067 TCID IS REQUIRED</p> <p>2. If populated and vv ≠ 1, then return error: FTRIS068 TCID VALID VALUE FOR INITIAL OCCURRENCE = 1</p> <p>3. If populated and TC OPT is not T return error message FTRIS222 TCID IS NOT ALLOWED IF TC OPT IS NOT T</p>	O
043	TC_NAME - Transfer of Calls To Name		Alphanumeric	1-35		<p>1. If not populated and TC_OPT = T, then return error: FTRIS069 TC NAME IS REQUIRED</p> <p>2. If populated and dl > 35, then return error: FTRIS070 TC NAME VALID LENGTH = 1-35</p> <p>3. If populated and TC OPT is not T return error message FTRIS223 TC NAME IS NOT ALLOWED IF TC OPT IS NOT T</p>	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
041	TC_PER - Transfer of Calls Period		Numeric	8-8	CCYYMMDD CC – 00-99 YY – 00-99 MM – 01-12 DD – 01-31	1. If populated and TC_TO_PRI is not populated, then return error: FTRIS077 TC PER IS PROHIBITED 2. If populated and format ≠ CCYYMMDD, then return error: FTRIS078 TC PER VALID FORMAT = CCYYMMDD	O
}							
TRANSFER OF CALLS_SEC {							
040	TC_TO_SEC - Transfer of Calls To Secondary Number		Numeric	10-10		1. If not populated and TC_OPT = T, then return error: FTRIS071 TC TO SEC IS REQUIRED 2. If populated and (dl ≠ 10 or dc ≠ numeric), then return error: FTRIS072 TC TO SEC VALID VALUE = 10 NUMERIC	O
042a	TCID2 - Transfer of Calls To Identifier		Numeric	1-2		1. If not populated and TC_OPT = T, then return error: FTRIS073 TCID 2 IS REQUIRED 2. If populated and all occurrences of data are not sequential and first occurrence does not equal 2, then return error: FTRIS074 TCID2 MUST BEGIN WITH 2 AND BE SEQUENTIAL 3. If populated and TC OPT is not T return error message FTRIS224 TCID2 IS NOT ALLOWED IF TC OPT IS NOT T	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
043a	TC_NAME2 - Transfer of Calls To Name		Alphanumeric	1-35		1. If not populated and TC_OPT = T, then return error: FTRIS075 TC NAME 2 IS REQUIRED 2. If populated and dl > 35, then return error: FTRIS076 TC NAME2 VALID LENGTH = 1-35 3. If populated and TC opt is not T return error message FTRIS225 TCNAME2 IS NOT ALLOWED IF TC OPT IS NOT T	O
}							
044	LEAN - Line Existing Account Number	DO NOT MAP				NOT SUPPORTED BY FTR	
045	LEATN - Line Existing Account Telephone Number	DO NOT MAP				NOT SUPPORTED BY FTR	
046	ST - Switch Type		Numeric	1-1	1, 2, 3, 4, 5	1. If not populated and position 2 of LSR.TOS = H then return error: FTRIS083 ST IS REQUIRED 2. If populated and position 2 of LSR.TOS ≠ H then return error: FTRIS084 ST IS PROHIBITED 3. If populated and vv ≠ 1, 2, 3, 4, 5, then return error: FTRIS085 ST VALID VALUE = 1, 2, 3, 4, 5	O
047	ANSA - Alternate Network Serving Arrangement		Alpha	1-1	Y	1. If populated and position 2 of LSR.TOS ≠ H then return error: FTRIS086 ANSA IS PROHIBITED 2. If populated and vv ≠ Y, then return error: FTRIS087 ANSA VALID VALUE =	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						Y	
048	TTY - Terminal Type		Alpha	1-1	A, B, C, D, E	1. If not populated and ST = 1, then return error: FTRIS088 TTY IS REQUIRED 2. If populated and ST ≠ 1, then return error: FTRIS089 TTY IS PROHIBITED 3. If populated and vv ≠ A, B, C, D, E, then return error: FTRIS090 TTY VALID VALUE = A, B, C, D, E	O
049	DISP - Display		Alpha	1-1	Y	1. If populated and TTY is not populated, then return error: FTRIS091 DISP IS PROHIBITED 2. If populated and vv ≠ Y, then return error: FTRIS092 DISP VALID VALUE = Y	O
050	DAT - Display Attributes		Alpha	1-1	A, B, C, D	1. If populated and vv ≠ A, D and ITYP = B, then return error: FTRIS093 DAT VALID VALUE = A, D 2. If populated and vv ≠ A, B, C, D, then return error: FTRIS094 DAT VALID VALUE = A, B, C, D	O
051	RP - Ring Preference		Alpha	1-1	A, B	1. If not populated and DAT = D, then return error: FTRIS095 RP IS REQUIRED 2. If populated and DAT ≠ D, then return error: FTRIS096 RP IS PROHIBITED 3. If populated and vv ≠ A, B, then return error: FTRIS098 RP VALID VALUE = A, B	O
052	TCGN - Terminal Configuration Group Name		Numeric	1-1	1, 2	1. If populated and vv ≠ 1, 2, then return error: FTRIS099 TCGN VALID VALUE = 1, 2	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
053	MAXB - Maximum B Channels		Numeric	1-1	1-8	<p>1. If not populated and LNA = N and position 2 of LSR.TOS = H then return error: FTRIS100 MAXB IS REQUIRED</p> <p>2. If populated and vv ≠ 1-8, then return error: FTRIS101 MAXB VALID VALUE = 1-8</p>	O
053a	MINB - Minimum B		N	2	1-23	<p>1. If populated and (dl > 2 or vv ≠ 1-23), then return error: FTRIS262 MINB VALID VALUE = 1-23</p> <p>2. If not populated and LNA = N, V, T and character 2 of LSR.TOS = K and IS.PRITYP = B, C, D, then return error: FTRIS263 MINB IS REQUIRED</p>	
054	DPG - Dialing Plan Group	DO NOT MAP				NOT SUPPORTED BY FTR	
055	TGID - Terminal Group Name	DO NOT MAP				NOT SUPPORTED BY FTR	
056	TGS - Terminal Group Station Restriction	DO NOT MAP				NOT SUPPORTED BY FTR	
057	CSD - Circuit Switched Data		Alpha	1-1	A, B, C	<p>1. If not populated and LNA = N and position 2 of LSR.TOS = H then return error: FTRIS112 CSD IS REQUIRED</p> <p>2. If populated and ((LNA ≠ N, C, V) or (position 2 of LSR.TOS ≠ H)), then return error: FTRIS113 CSD IS PROHIBITED</p> <p>3. If populated and vv ≠ A, B, C, then return error: FTRIS114 CSD VALID VALUE = A, B, C</p>	O
058	CSDC - Circuit		Alpha	1-1	A, B, C	1. If not populated and CSD is populated,	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
	Switched Data Configuration					<p>then return error: FTRIS115 CSDC IS REQUIRED</p> <p>2. If populated and CSD is not populated, then return error: FTRIS116 CSDC IS PROHIBITED</p> <p>3. If populated and vv ≠ A, B, C, then return error: FTRIS117 CSDC VALID VALUE = A, B, C</p>	
059	CSV - Circuit Switched Voice		Alpha	1-1	A, B	<p>1. If not populated and LNA = N and position 2 of LSR.TOS = H then return error: FTRIS118 CSV IS REQUIRED</p> <p>2. If populated and ((LNA ≠ N, C, V) or (position 2 of LSR.TOS ≠ H)), then return error: FTRIS119 CSV IS PROHIBITED</p> <p>3. If populated and vv ≠ A, B, then return error: FTRIS120 CSV VALID VALUE = A, B</p>	O
060	CSVC - Circuit Switched Voice Configuration		Alpha	1-1	A, B, C, D	<p>1. If not populated and CSV is populated, then return error: FTRIS121 CSVC IS REQUIRED</p> <p>2. If populated and CSV is not populated, then return error: FTRIS122 CSVC IS PROHIBITED</p> <p>3. If populated and vv ≠ A and CSV = A, then return error: FTRIS123 CSVC VALID VALUE MUST = A WHEN CSV = A</p> <p>4. If populated and vv ≠ A, B, C, D, then</p>	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						return error: FTRIS124 CSVK VALID VALUE = A, B, C, D	
061	ITYP - ISDN Type		Alpha	1-1	A, B, C, D	<p>1. If not populated and LNA = N and position 2 of LSR.TOS = H then return error: FTRIS125 ITYP IS REQUIRED</p> <p>2. If populated and ((LNA ≠ N, C, V) or (position 2 of LSR.TOS ≠ H)), then return error: FTRIS126 ITYP IS PROHIBITED</p> <p>3. If populated and vv ≠ A, B, C, D, then return error: FTRIS127 ITYP VALID VALUE = A, B, C, D</p>	O
062	BS - Bearer Service		Alpha	1-1	A, B, C, D, E, F	<p>1. If not populated and LNA = N and position 2 of LSR.TOS = H then return error: FTRIS128 BS IS REQUIRED</p> <p>2. If populated and ((LNA ≠ N, C, V) or (position 2 of LSR.TOS ≠ H)), then return error: FTRIS129 BS IS PROHIBITED</p> <p>3. If populated and vv ≠ A, B, C, D, E, F, then return error: FTRIS130 BS VALID VALUE = A, B, C, D, E, F</p>	O
062a	BCAP – Bearer Capability		Alpha	1-1	A, B	<p>1. If populated and vv ≠ A, B, then return error: FTRIS264 BCAP VALID VALUE = A, B</p> <p>2. If not populated and LNA = N, V, T and character 2 of LSR.TOS = K, then return error: FTRIS265 BCAP IS REQUIRED WHEN LNA = N, V, T AND LSR.TOS = K</p>	
063	DSNA - Digital Services Network		Alphanumeric	1-18		1. If not populated and LNA = N and position 2 of LSR.TOS = H then return	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
	Assignment					<p>error: FTRIS131 DSNA IS REQUIRED</p> <p>2. If populated and ((LNA ≠ N, C, V) or (position 2 of LSR.TOS ≠ H)), then return error: FTRIS132 DSNA IS PROHIBITED</p> <p>3. If populated and dl > 18, then return error: FTRIS133 DSNA VALID LENGTH = 1-18</p>	
064	EKTS - Electronic Key Telephone Set		Alpha	1-1	A, B	<p>1. If not populated and ITYP = B, C, D, then return error: FTRIS134 EKTS IS REQUIRED</p> <p>2. If populated and ITYP ≠ B, C, D, then return error: FTRIS135 EKTS IS PROHIBITED</p> <p>3. If populated and vv ≠ A, B, then return error: FTRIS136 EKTS VALID VALUE = A, B</p>	O
065	CAPP - Call Appearance		Numeric	6-6		<p>1. If not populated and EKTS is populated and ST = 1, then return error: FTRIS137 CAPP IS REQUIRED</p> <p>2. If populated and (EKTS is not populated or ST ≠ 1), then return error: FTRIS138 CAPP IS PROHIBITED</p> <p>3. If populated and (dl ≠ 6 or dc ≠ numeric), then return error: FTRIS139 CAPP VALID VALUE = 6 NUMERIC</p>	O
066	DCLS - Digital Subscriber Line Class of Service		Alpha	1-1	A, B, C	<p>1. If not populated and ST = 1, then return error: FTRIS140 DCLS IS REQUIRED</p>	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						<p>2. If populated and ST ≠ 1, then return error: FTRIS141 DCLS IS PROHIBITED</p> <p>3. If populated and vv ≠ A, B, C, then return error: FTRIS142 DCLS VALID VALUE = A, B, C</p>	
067	MDPK - Maximum D Channel Packet Users		Numeric	1-1	1-8	<p>1. If not populated and DCLS is populated, then return error: FTRIS143 MDPK IS REQUIRED</p> <p>2. If populated and DCLS is not populated, then return error: FTRIS144 MDPK IS PROHIBITED</p> <p>3. If populated and vv ≠ 1 and DCLS = A, then return error: FTRIS145 MDPK VALID VALUE = 1</p> <p>4. If populated and vv ≠ 1-8, then return error: FTRIS146 MDPK VALID VALUE = 1-8</p>	O
068	MTER - Maximum Terminals		Numeric	1-1	1-8	<p>1. If not populated and DCLS is populated, then return error: FTRIS147 MTER IS REQUIRED</p> <p>2. If populated and DCLS is not populated, then return error: FTRIS148 MTER IS PROHIBITED</p> <p>3. If populated and vv ≠ 1 and DCLS = A, then return error: FTRIS149 MTER VALID VALUE = 1</p> <p>4. If populated and vv ≠ 1-8, then return</p>	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						error: FTRIS150 MTER VALID VALUE = 1-8	
069	DO - Digits Out		Numeric	1-2		<p>1. If not populated and LNA = N and (position 2 of LSR.TOS = K then return error: FTRIS151 DO IS REQUIRED</p> <p>2. If populated and ((LNA ≠ N, C, V) or (position 2 of LSR.TOS ≠ K)), then return error: FTRIS152 DO IS PROHIBITED</p> <p>3. If populated and (dl > 2 or dc ≠ numeric), then return error: FTRIS153 DO VALID VALUE = 1-2 NUMERIC</p>	O
070	GL - Glare		Alpha	1-1	A, B, C	<p>1. If populated and vv = C and LNA ≠ C, V, then return error: FTRIS154 GL VALID VALUE = A, B</p> <p>2. If populated and position 2 of LSR.TOS ≠ K then return error: FTRIS155 GL IS PROHIBITED</p> <p>3. If populated and vv ≠ A, B, C, then return error: FTRIS156 GL VALID VALUE = A, B, C</p>	O
071	PMS - Primary Rate Interface ISDN (PRI) Method Selection		Alpha	1-1	A, B, C, D, E, F	<p>1. If not populated and LNA = N and position 2 of LSR.TOS = K then return error: FTRIS157 PMS IS REQUIRED</p> <p>2. If populated and ((LNA ≠ N, C,V) or (position 2 of LSR.TOS ≠ K)), then return error: FTRIS158 PMS IS PROHIBITED</p> <p>3. If populated and vv ≠ A, B, C, D, E, F, then return error: FTRIS159 PMS VALID</p>	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						VALUE = A, B, C, D, E, F	
071a	CLOCK – Clocking		Alpha	1	Y, N	<p>1. If not populated and LNA = N, V and position 2 of LSR.TOS = K then return error: FTRIS226 CLOCK IS REQUIRED</p> <p>2. If populated and ((LNA ≠ N,V) or (position 2 of LSR.TOS ≠ K)), then return error: FTRIS227 CLOCK IS PROHIBITED</p> <p>3. If populated and vv is not Y, N return error message FTRIS228 CLOCK VALID VALUE IS Y OR N</p>	
072	PCT- Primary Rate Interface (PRI) Call Type		Alpha	1-1	A, B, C	<p>1. If not populated and LNA = N and position 2 of LSR.TOS = K then return error: FTRIS160 PCT IS REQUIRED</p> <p>2. If populated and ((LNA ≠ N, C, V) or (position 2 of LSR.TOS ≠ K)), then return error: FTRIS161 PCT IS PROHIBITED</p> <p>3. If populated and vv ≠ A, B, C, then return error: FTRIS162 PCT VALID VALUE = A, B, C</p>	O
072a	PRITYP – PRI Type		Alpha	1-1	A, B, C, D	<p>1. If populated and vv is not A, B, C, D return error message FTRIS229 PRITYP VALID VALUE IS A, B, C OR D</p> <p>2. If not populated and LNA = N, V and position 2 of LSR.TOS = K and BS, PCT, PRIBD is populated return error message FTRIS230 PRITYP IS REQUIRED</p>	
073	DRI - Digital Route Index		Alpha	1-1	Y	<p>1. If populated and ((LNA ≠ N, C, V) or (position 2 of LSR.TOS ≠ K)), then return</p>	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						error: FTRIS163 DRI IS PROHIBITED 2. If populated and vv ≠ Y, then return error: FTRIS164 DRI VALID VALUE = Y	
074	TA - Terminating Arrangement		Alpha	1-1	A, B, C, D, E, F	1. If populated and ((LNA ≠ N, C, V) or (position 2 of LSR.TOS ≠ K) or (LSR.P ≠ A, D)), then return error: FTRIS165 TA IS PROHIBITED 2. If populated and vv ≠ A, B, C, D, E, F, then return error: FTRIS166 TA VALID VALUE = A, B, C, D, E, F	O
075	PRIBD - ISDN PRI "B" and "D" Channel Configuration		Alphanumeric	7-7	NNNNNNA	1. If not populated and LNA = N and position 2 of LSR.TOS = K then return error: FTRIS167 PRIBD IS REQUIRED 2. If populated and ((LNA ≠ N, C, V) or (position 2 of LSR.TOS ≠ K)), then return error: FTRIS168 PRIBD IS PROHIBITED 3. If populated and format ≠ NNNNNNA, then return error: FTRIS169 PRIBD VALID FORMAT = NNNNNNA	O
076	ISPID - ISDN Service Profile Identification		Alphanumeric	1-15		1. If not populated and LNA = N and position 2 of LSR.TOS = H then return error: FTRIS170 ISPID IS REQUIRED 2. If populated and ((LNA ≠ N, C, V) or (position 2 of LSR.TOS ≠ H)), then return error: FTRIS171 ISPID IS PROHIBITED 3. If populated and dl > 15, then return error: FTRIS172 ISPID VALID LENGTH = 1-15	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
077	PKG - Package		Alphanumeric	1-12		1. If not populated and LNA = N and position 2 of LSR.TOS = H then return error: FTRIS173 PKG IS REQUIRED 2. If populated and ((LNA ≠ N, C, V) or (position 2 of LSR.TOS ≠ H)), then return error: FTRIS174 PKG IS PROHIBITED 3. If populated and dl > 12, then return error: FTRIS175 PKG VALID LENGTH = 1-12	O
078	JR - Jack Request	DO NOT MAP				NOT SUPPORTED BY FTR	
079	JK_CODE - Jack Code	DO NOT MAP				NOT SUPPORTED BY FTR	
080	JK_NUM - Jack Number	DO NOT MAP				NOT SUPPORTED BY FTR	
081	JK_POS - Jack Position	DO NOT MAP				NOT SUPPORTED BY FTR	
082	NIDR - NID Request		Alpha	1-1	Y	1. If populated and vv ≠ Y, then return error: FTRIS184 NIDR VALID VALUE = Y 2. If populated and LNA is not N return error message FTRIS231 NIDR IS NOT ALLOWED IF LNA IS NOT N	O
083	IWJQ - Inside Wire Jack Quantity		Numeric	2-2	01-99	1. If populated and vv ≠ 01-99, then return error: FTRIS185 IWJQ VALID VALUE = 01-99 2. If populated and IWJK is not populated return error message FTRIS232 IWJQ IS NOT ALLOWED IF IWJK IS NOT POPULATED	O
084	IWJK - Inside Wire Jack Code		Alphanumeric	1-5		1. If populated and LSR.ACT is not C, N, T, V and LSR.P is not A, C, D and LNA is	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						not N, V, C return error message FTRIS186 IWJK IS PROHIBITED 2. If populated and dl > 5, then return error: FTRIS188 IWJK VALID LENGTH = 1-5	
085	IWT - Inside Wire Type	DO NOT MAP				NOT SUPPORTED BY FTR	
086	LSCP - Local Service Provider Change Prohibited		Alpha	1-1	A, B	1. If populated and LNA is D, X, P return error: FTRIS191 LSCP IS PROHIBITED 2. If populated and vv ≠ A, B, then return error: FTRIS192 LSCP VALID VALUE = A, B	O
087	BA - Blocking Activity		Alpha	1-1	A, D, E, N	1. If populated and vv ≠ A, D, E, N, then return error: FTRIS193 BA VALID VALUE = A, D, E, N 2. If populated and vv is not A and LNA is N return error message FTRIS187 BA MUST BE A WHEN LNA IS N 3. If populated and vv is not A, E and LNA is V return error message FTRIS259 BA MUST BE A OR E WHEN LNA IS V	O
088	BLOCK - Block		Alpha, Numeric	1-16	A, B, C, D, E, F, G, H, J, K, L, M, N, P, Q, R, S, T, U, V, W, X, Y, Z, 1	1. If not populated and BA = A, D, E then return error: FTRIS194 BLOCK IS REQUIRED 2. If populated and BA ≠ A, D, E then return error: FTRIS195 BLOCK IS PROHIBITED	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						3. If populated and (dl > 16 or vv does not contain A, B, C, D, E, F, G, H, J, K, L, M, N, P, Q, R, S, T, U, V, W, X, Y, Z, 1), then return error: FTRIS196 BLOCK VALID LENGTH = 1-16. VALID VALUES = A, B, C, D, E, F, G, H, J, K, L, M, N, P, Q, R, S, T, U, V, W, X, Y, Z, 1	
089	CC_ACT - Calling Card Activity	DO NOT MAP				NOT SUPPORTED BY FTR	
090	CC_NO - Calling Card Number	DO NOT MAP				NOT SUPPORTED BY FTR	
091	CCT - Calling Card Type	DO NOT MAP				NOT SUPPORTED BY FTR	
092	CCDD - Calling Card Disconnect Date	DO NOT MAP				NOT SUPPORTED BY FTR	
093	FLI - Foreign Language Indicator	DO NOT MAP				NOT SUPPORTED BY FTR	
094	DI	DO NOT MAP				NOT SUPPORTED BY FTR	
095	CNAM	DO NOT MAP				NOT SUPPORTED BY FTR	
096	BSPRAO	DO NOT MAP				NOT SUPPORTED BY FTR	
097	CFA	DO NOT MAP				NOT SUPPORTED BY FTR	
097a	TGN – Trunk Group		Alphanumeric	1-4		<p>1. If populated and dl> 4 return error message FTRIS233 TGN MAY NOT EXCEED 4 CHARACTERS</p> <p>2. If not populated and LNA = N, V and position 2 of LSR.TOS = K then return error: FTRIS234 TGN IS REQUIRED</p> <p>3. If populated and ((LNA ≠ N, V) or (position 2 of LSR.TOS ≠ K)), then return error: FTRIS235 TGN IS PROHIBITED</p>	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
097b	PULSE – Type of Pulsing		Alpha	2-4	DP, MF, DTMF	<p>1. If populated and vv is not DP, MF, DTMF return error message FTRIS236 PULSE VALID VALUES ARE DP, MF OR DTMF</p> <p>2. If not populated and LNA is N, V return error message FTRIS237 PULSE IS REQUIRED WHEN LNA IS N OR V</p> <p>3. If populated and LNA is not N, V return error message FTRIS238 PULSE IS NOT ALLOWED IF LNA IS NOT N OR V</p>	O
097c	SSIG – Start Signaling		Alpha	2-2	LS, GS, WS, DD, IM	<p>1. If populated and vv is not LS, GS, WS, DD, IM return error message FTRIS239 SSIG VALID VALUES ARE LS, GS, WS, DD OR IM</p> <p>2. If populated and vv is not GS, LS and SGNL = LP return error message FTRIS240 SSIG MUST BE GS OR LS WHEN SGNL IS LP</p> <p>3. If populated and vv = WS, DD, IM and SGNL is not E1, E2, E3 return error message FTRIS241 SSIG MAY ONLY BE WS, DD OR IM WHEN SGNL IS E1, E2 OR E3</p> <p>4. If populated and LSR.ACT = W return error message FTRIS242 SSIG IS NOT ALLOWED WHEN ACT IS W</p>	O
097d	SGNL – Signaling		Alphanumeric	2-2	LP, E1, E2, E3	<p>1. If populated and vv is not LP, E1, E2, E3 return error message FTRIS243 SGNL VALID VALUES ARE LP, E1, E2 OR E3</p>	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						<p>2. If populated and vv is not LP and SSIG is LS, GS return error message FTRIS244 SGNL MUST BE LP WHEN SSIG IS LS OR GS</p> <p>3. If populated and vv is not E1, E2, E3 and SSIG is WS, DD, IM return error message FTRIS245 SGNL MUST BE E1, E2 OR E3 WHEN SSIG IS WS, DD OR IM</p> <p>4. If not populated and LNA is N, V and position 2 of LSR.TOS is K return error message FTRIS246 SGNL IS REQUIRED</p> <p>5. If populated and ((LNA ≠ N,) or (position 2 of LSR.TOS ≠ K)), then return error: FTRIS247 SGNL IS PROHIBITED</p>	
097e	DCBU – D Channel Backup		Alpha	1	Y, N	<p>1. If populated and vv is not Y, N return error message FTRIS248 DCBU VALID VALUES ARE Y OR N</p> <p>2. If not populated and LNA is N, V and position 2 of LSR.TOS is K return error message FTRIS249 DCBU IS REQUIRED</p> <p>3. If populated and ((LNA ≠ N,) or (position 2 of LSR.TOS ≠ K)), then return error: FTRIS250 DCBU IS PROHIBITED</p>	O
097f	IFEAT – Optional ISDN Features		Alpha	1-5	A, B, C, D, E	<p>1. If populated and vv is not A, B, C, D, E return error message FTRIS251 IFEAT VALID VALUES ARE A, B, C, D OR E</p>	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						2. If populated and dl > 5 return error message FTRIS252 IFEAT MAY NOT EXCEED 5 CHARACTERS	
097g	IFEATNBR - ISDN Feature Number		Alphanumeric (including hyphen)	15	NPANXXXXXX or NPANXXXXXX-XXXX	1. If populated and vv ≠ NPANXXXXXX or NPANXXXXXX-XXXX, then return error: FTRIS266 IFEATNBR VALID VALUE = NPANXXXXXX or NPANXXXXXX-XXXX 2. If not populated and IFEAT = A, B, then return error: FTRIS267 IFEATNBR IS REQUIRED WHEN IFEAT = A OR B	
097h	PRIHUNT – PRI Hunting		Numeric	1, 2	1,2,3,4,5,6,7,8,9,10	1. If populated and vv is not 1,2,3,4,5,6,7,8,9,10 return error message FTRIS253 PRIHUNT MUST BE 1,2,3,4,5,6,7,8,9 OR 10	
098	FA - Feature Activity		Alpha	1-1	N, C, D, V	1. If populated and vv ≠ N, C, D, V then return error: FTRIS211 FA VALID VALUE = N, C, D, V 2. If populated and vv is not N, C, D and LNA is C return error message FTRIS254 FA MUST BE N, C OR D WHEN LNA IS C 3. If populated and vv is not N and LNA is N return error message FTRIS255 FA MUST BE N WHEN LNA IS N 4. If populated and vv is not N, V and LNA is V return error message FTRIS256 FA MAY ONLY BE N OR V WHEN LNA IS V 5. If populated and LNA is P, D, X return	O

Field Number	Field Name	Mapping Rule	Data Char	Field Length	Valid Values / Range of Values	Conditional Business Rules / Edits	R/O/P
						error message FTRIS257 FA IS NOT ALLOWED WITH THIS LNA	
099	FEATURE - Feature Codes		Alphanumeric	1-6		1. If not populated and FA is populated, then return error: FTRIS212 FEATURE IS REQUIRED 2. If populated and FA is not populated, then return error: FTRIS213 FEATURE IS PROHIBITED 3. If populated and dl > 6, then return error: FTRIS214 FEATURE VALID LENGTH = 1-6	O
100	FEATURE_DETAIL - Feature Detail		Alphanumeric	1-200		1. If populated and FEATURE is not populated, then return error: FTRIS215 FEATURE DETAIL IS PROHIBITED 3. If populated and dl > 200, then return error: FTRIS216 FEATURE DETAIL VALID LENGTH = 1-200	O

APPENDIX A – ERROR MESSAGE TABLE

Error Message Number	Error Message Text
FTRIS001	IQTY IS REQUIRED
FTRIS002	IQTY VALID VALUE = 1-5 NUMERIC
FTRIS003	NPI VALID VALUES ARE C, E OR F
FTRIS004	NPI IS REQUIRED WHEN NPDI IS B OR D
FTRIS005	NPI IS NOT ALLOWED WHEN NPDI IS NOT B OR D
FTRIS006	LNA MAY NOT BE V IF LSR ACT IS C
FTRIS007	LNA MUST BE N WHEN LSR ACT IS N
FTRIS008	LOCNUM IS REQUIRED
FTRIS009	LOCNUM VALID VALUE = 1-3 NUMERIC
FTRIS010	LNUM IS REQUIRED
FTRIS011	LNUM VALID VALUE = 1-5 NUMERIC
FTRIS012	LNA MUST BE V, N OR D WHEN LSR ACT IS V
FTRIS013	
FTRIS014	NPI VALID VALUE = C, D, E
FTRIS015	LNA IS REQUIRED
FTRIS016	LNA VALID VALUE = C, D, N, V, W, X, P
FTRIS017	LTOS IS REQUIRED
FTRIS018	LTOS IS PROHIBITED
FTRIS019	LTOS VALID VALUE POSITION 1 = 1, 2, 3, 5
FTRIS020	LTOS VALID VALUE POSITION 2 = H, K
FTRIS021	LTOS VALID VALUE POSITION 3 = F, G, M, HYPHEN (-)
FTRIS022	LTOS VALID VALUE POSITION 4 = F, N, Y, Z, HYPHEN (-)
FTRIS023	LTOS VALID LENGTH = 4
FTRIS024	SOE VALID VALUE = 1-2 NUMERIC
FTRIS025	NOTYP IS REQUIRED
FTRIS026	NOTYP IS PROHIBITED
FTRIS027	NOTYP VALID VALUE = A, B, C
FTRIS028	TNS IS REQUIRED
FTRIS029	TNS VALID LENGTH = 1-15
FTRIS030	PN VALID LENGTH = 10
FTRIS031	DTN VALID LENGTH = 1-10
FTRIS032	S VALID VALUE = A, B, C
FTRIS033	SPLD IS PROHIBITED

FTRIS034	SPLD IS PROHIBITED
FTRIS035	SPLD IS PROHIBITED
FTRIS036	SPLD VALID VALUE = A, B, C
FTRIS037	OTN IS REQUIRED
FTRIS038	OTN VALID VALUE = 10 NUMERIC
FTRIS039	DOTN IS REQUIRED
FTRIS040	DOTN VALID VALUE = 10 NUMERIC
FTRIS041	TSP ISPROHIBITED WITH LNA OF P OR X
FTRIS042	TSP IS NOT ALLOWED WITH THIS TOS
FTRIS043	TERS VALID LENGTH = 1-10
FTRIS044	TSP VALID FORMAT = XXXXXXXXX-XN
FTRIS045	TSP VALID VALUE FOR POSITION 11 = E, 0, 1, 2, 3, 4, 5
FTRIS046	TSP VALID VALUE FOR POSITION 12 = 0, 1, 2, 3, 4, 5
FTRIS047	SAN VALID LENGTH = 1-30
FTRIS048	CKR VALID LENGTH = 1-41
FTRIS049	ECCKT MAY NOT EXCEED 41 CHARACTERS
FTRIS050	RL IS PROHIBITED
FTRIS051	RL VALID VALUE = Y
FTRIS052	OECCKT IS REQUIRED
FTRIS053	OECCKT IS PROHIBITED
FTRIS054	OECCKT MAY NOT EXCEED 41 CHARACTERS
FTRIS055	FPI VALID VALUE = A, B, E, R, S, T
FTRIS056	PIC IS REQUIRED
FTRIS057	PIC VALID VALUE = NONE, NC OR 2-4 NUMERIC
FTRIS058	LPIC IS REQUIRED
FTRIS059	LPIC VALID VALUE = NONE, NC OR 2-4 NUMERIC
FTRIS060	IPIC VALID LENGTH = 2-4
FTRIS061	SDI VALID VALUE = E, F, G, H, I, J, K, L, M
FTRIS062	MATN IS PROHIBITED
FTRIS063	MATN VALID VALUE = A, M
FTRIS064	TC OPT VALID VALUE = N, S, T
FTRIS065	TC TO PRI IS REQUIRED
FTRIS066	TC TO PRI VALID VALUE = 10 NUMERIC
FTRIS067	TCID IS REQUIRED
FTRIS068	TCID VALID VALUE FOR INITIAL OCCURRENCE = 1

FTRIS069	TC NAME IS REQUIRED
FTRIS070	TC NAME VALID LENGTH = 1-35
FTRIS071	TC TO SEC IS REQUIRED
FTRIS072	TC TO SEC VALID VALUE = 10 NUMERIC
FTRIS073	TCID 2 IS REQUIRED
FTRIS074	TCID2 MUST BEGIN WITH 2 AND BE SEQUENTIAL
FTRIS075	TC NAME 2 IS REQUIRED
FTRIS076	TC NAME2 VALID LENGTH = 1-35
FTRIS077	TC PER IS PROHIBITED
FTRIS078	TC PER VALID FORMAT = CCYYMMDD
FTRIS079	LEAN IS PROHIBITED
FTRIS080	LEAN VALID LENGTH = 1-20
FTRIS081	LEATN IS PROHIBITED
FTRIS082	LEATN VALID VALUE = 10 NUMERIC
FTRIS083	ST IS REQUIRED
FTRIS084	ST IS PROHIBITED
FTRIS085	ST VALID VALUE = 1, 2, 3, 4, 5
FTRIS086	ANSA IS PROHIBITED
FTRIS087	ANSA VALID VALUE = Y
FTRIS088	TTYP IS REQUIRED
FTRIS089	TTYP IS PROHIBITED
FTRIS090	TTYP VALID VALUE = A, B, C, D, E
FTRIS091	DISP IS PROHIBITED
FTRIS092	DISP VALID VALUE = Y
FTRIS093	DAT VALID VALUE = A, D
FTRIS094	DAT VALID VALUE = A, B, C, D
FTRIS095	RP IS REQUIRED
FTRIS096	RP IS PROHIBITED
FTRIS097	RP VALID VALUE = B
FTRIS098	RP VALID VALUE = A, B
FTRIS099	TCGN VALID VALUE = 1, 2
FTRIS100	MAXB IS REQUIRED
FTRIS101	MAXB VALID VALUE = 1-8
FTRIS102	DPG IS REQUIRED
FTRIS103	DPG IS PROHIBITED

FTRIS104	DPG VALID LENGTH = 1-8
FTRIS105	TGID IS REQUIRED
FTRIS106	TGID IS PROHIBITED
FTRIS107	TGID VALID VALUE = 1-4 NUMERIC
FTRIS108	TGS IS REQUIRED
FTRIS109	TGS IS PROHIBITED
FTRIS110	TGS MUST BE 3 CHARACTERS WHEN FIRST CHARACTER = B, C
FTRIS111	TGS VALID LENGTH = 2-3. VALID VALUE = A, B, C
FTRIS112	CSD IS REQUIRED
FTRIS113	CSD IS PROHIBITED
FTRIS114	CSD VALID VALUE = A, B, C
FTRIS115	CSDC IS REQUIRED
FTRIS116	CSDC IS PROHIBITED
FTRIS117	CSDC VALID VALUE = A, B, C
FTRIS118	CSV IS REQUIRED
FTRIS119	CSV IS PROHIBITED
FTRIS120	CSV VALID VALUE = A, B
FTRIS121	CSVC IS REQUIRED
FTRIS122	CSVC IS PROHIBITED
FTRIS123	CSVC VALID VALUE MUST = A WHEN CSV = A
FTRIS124	CSVC VALID VALUE = A, B, C, D
FTRIS125	ITYP IS REQUIRED
FTRIS126	ITYP IS PROHIBITED
FTRIS127	ITYP VALID VALUE = A, B, C, D
FTRIS128	BS IS REQUIRED
FTRIS129	BS IS PROHIBITED
FTRIS130	BS VALID VALUE = A, B, C, D, E, F
FTRIS131	DSNA IS REQUIRED
FTRIS132	DSNA IS PROHIBITED
FTRIS133	DSNA VALID LENGTH = 1-18
FTRIS134	EKTS IS REQUIRED
FTRIS135	EKTS IS PROHIBITED
FTRIS136	EKTS VALID VALUE = A, B
FTRIS137	CAPP IS REQUIRED
FTRIS138	CAPP IS PROHIBITED

FTRIS139	CAPP VALID VALUE = 6 NUMERIC
FTRIS140	DCLS IS REQUIRED
FTRIS141	DCLS IS PROHIBITED
FTRIS142	DCLS VALID VALUE = A, B, C
FTRIS143	MDPK IS REQUIRED
FTRIS144	MDPK IS PROHIBITED
FTRIS145	MDPK VALID VALUE = 1
FTRIS146	MDPK VALID VALUE = 1-8
FTRIS147	MTER IS REQUIRED
FTRIS148	MTER IS PROHIBITED
FTRIS149	MTER VALID VALUE = 1
FTRIS150	MTER VALID VALUE = 1-8
FTRIS151	DO IS REQUIRED
FTRIS152	DO IS PROHIBITED
FTRIS153	DO VALID VALUE = 1-2 NUMERIC
FTRIS154	GL VALID VALUE = A, B
FTRIS155	GL IS PROHIBITED
FTRIS156	GL VALID VALUE = A, B, C
FTRIS157	PMS IS REQUIRED
FTRIS158	PMS IS PROHIBITED
FTRIS159	PMS VALID VALUE = A, B, C, D, E, F
FTRIS160	PCT IS REQUIRED
FTRIS161	PCT IS PROHIBITED
FTRIS162	PCT VALID VALUE = A, B, C
FTRIS163	DRI IS PROHIBITED
FTRIS164	DRI VALID VALUE = Y
FTRIS165	TA IS PROHIBITED
FTRIS166	TA VALID VALUE = A, B, C, D, E, F
FTRIS167	PRIBD IS REQUIRED
FTRIS168	PRIBD IS PROHIBITED
FTRIS169	PRIBD VALID FORMAT = NNNNNNA
FTRIS170	ISPID IS REQUIRED
FTRIS171	ISPID IS PROHIBITED
FTRIS172	ISPID VALID LENGTH = 1-15
FTRIS173	PKG IS REQUIRED

FTRIS174	PKG IS PROHIBITED
FTRIS175	PKG VALID LENGTH = 1-12
FTRIS176	JR VALID VALUE = Y
FTRIS177	JK CODE IS REQUIRED
FTRIS178	JK CODE IS PROHIBITED
FTRIS179	JK CODE VALID LENGTH = 1-5
FTRIS180	JK NUM IS REQUIRED
FTRIS181	JK NUM VALID VALUE = 1-2 ALPHA, NUMERIC
FTRIS182	JK POS IS REQUIRED
FTRIS183	JK POS VALID VALUE = 1-2 NUMERIC
FTRIS184	NIDR VALID VALUE = Y
FTRIS185	IWJQ VALID VALUE = 01-99
FTRIS186	IWJK IS PROHIBITED
FTRIS187	BA MUST BE A WHEN LNA IS N
FTRIS188	IWJK VALID LENGTH = 1-5
FTRIS189	IWT IS REQUIRED
FTRIS190	IWT VALID VALUE = A, B, C, D, E
FTRIS191	LSCP IS PROHIBITED
FTRIS192	LSCP VALID VALUE = A, B
FTRIS193	BA VALID VALUE = A, D, E, N
FTRIS194	BLOCK IS REQUIRED
FTRIS195	BLOCK IS PROHIBITED
FTRIS196	BLOCK VALID LENGTH = 1-16. VALID VALUES = A, B, C, D, E, F, G, H, J, K, L, M, N, P, Q, R, S, T, U, V, W, X, Y, Z, 1
FTRIS197	CC-ACT VALID VALUE = A, B, C
FTRIS198	CC-NO IS REQUIRED
FTRIS199	CC-NO IS PROHIBITED
FTRIS200	CC-NO VALID VALUE = 10, 14 NUMERIC
FTRIS201	CCT IS REQUIRED
FTRIS202	CCT IS PROHIBITED
FTRIS203	CCT VALID VALUE = A, B, C, D
FTRIS204	CCDD VALID FORMAT = CCYYMMDD
FTRIS205	FLI VALID LENGTH = 1-3
FTRIS206	DI VALID VALUE = A, B, C
FTRIS207	CNAM VALID LENGTH = 1-15
FTRIS208	BSPRAO IS PROHIBITED

FTRIS209	BSPRAO VALID LENGTH = 3
FTRIS210	CFA VALID LENGTH = 1-42
FTRIS211	FA VALID VALUE = N, C, D, V
FTRIS212	FEATURE IS REQUIRED
FTRIS213	FEATURE IS PROHIBITED
FTRIS214	FEATURE VALID LENGTH = 1-6
FTRIS215	FEATURE DETAIL IS PROHIBITED
FTRIS216	FEATURE DETAIL VALID LENGTH = 1-200
FTRIS217	TNS MUST BE N IF IT IS ONE ALPHA CHARACTER
FTRIS218	ECCKT IS PROHIBITED WHEN LNA IS P OR X
FTRIS219	ECCKT SPECIAL CHARACTERS MAY ONLY BE VIRGULE (FORWARD SLASH)
FTRIS220	VIRGULE MUST BE IMMEDIATELY PRECEDED AND FOLLOWED BY A NUMERIC
FTRIS221	TC TO PRI IS NOT ALLOWED IF TC OPT IS NOT T
FTRIS222	TCID IS NOT ALLOWED IF TC OPT IS NOT T
FTRIS223	TC NAME IS NOT ALLOWED IF TC OPT IS NOT T
FTRIS224	TCID2 IS NOT ALLOWED IF TC OPT IS NOT T
FTRIS225	TCNAME2 IS NOT ALLOWED IF TC OPT IS NOT T
FTRIS226	CLOCK IS REQUIRED
FTRIS227	CLOCK IS PROHIBITED
FTRIS228	CLOCK VALID VALUE IS Y OR N
FTRIS229	PRITYP VALID VALUE IS A, B, C OR D
FTRIS230	PRITYP IS REQUIRED
FTRIS231	NIDR IS NOT ALLOWED IF LNA IS NOT N
FTRIS232	IWJQ IS NOT ALLOWED IF IWJK IS NOT POPULATED
FTRIS233	TGN MAY NOT EXCEED 4 CHARACTERS
FTRIS234	TGN IS REQUIRED
FTRIS235	TGN IS PROHIBITED
FTRIS236	PULSE VALID VALUES ARE DP, MF OR DTMF
FTRIS237	PULSE IS REQUIRED WHEN LNA IS N OR V
FTRIS238	PULSE IS NOT ALLOWED IF LNA IS NOT N OR V
FTRIS239	SSIG VALID VALUES ARE LS, GS, WS, DD OR IM
FTRIS240	SSIG MUST BE GS OR LS WHEN SGNL IS LP
FTRIS241	SSIG MAY ONLY BE WS, DD OR IM WHEN SGNL IS E1, E2 OR E3
FTRIS242	SSIG IS NOT ALLOWED WHEN ACT IS W
FTRIS243	SGNL VALID VALUES ARE LP, E1, E2 OR E3

FTRIS244	SGNL MUST BE LP WHEN SSIG IS LS OR GS
FTRIS245	SGNL MUST BE E1, E2 OR E3 WHEN SSIG IS WS, DD OR IM
FTRIS246	SGNL IS REQUIRED
FTRIS247	SGNL IS PROHIBITED
FTRIS248	DCBU VALID VALUES ARE Y OR N
FTRIS249	DCBU IS REQUIRED
FTRIS250	DCBU IS PROHIBITED
FTRIS251	IFEAT VALID VALUES ARE A, B, C, D OR E
FTRIS252	IFEAT MAY NOT EXCEED 5 CHARACTERS
FTRIS253	PRIHUNT MUST BE 1,2,3,4,5,6,7,8,9 OR 10
FTRIS254	FA MUST BE N, C OR D WHEN LNA IS C
FTRIS255	FA MUST BE N WHEN LNA IS N
FTRIS256	FA MAY ONLY BE N OR V WHEN LNA IS V
FTRIS257	FA IS NOT ALLOWED WITH THIS LNA
FTRIS258	
FTRIS259	BA MUST BE A OR E WHEN LNA IS V
FTRIS260	DIDNBR VALID VALUE = 1 – 10000
FTRIS261	DIDNBR REQUIRED WHEN CHARACTER 2 OF TOS = K
FTRIS262	MINB VALID VALUE = 1-23
FTRIS263	MINB IS REQUIRED
FTRIS264	BCAP VALID VALUE = A, B
FTRIS265	BCAP IS REQUIRED WHEN LNA = N, V, T AND LSR.TOS = K
FTRIS266	IFEATNBR VALID VALUE = NPANXXXXXX or NPANXXXXXX-XXXX
FTRIS267	IFEATNBR IS REQUIRED WHEN IFEAT = A OR B

APPENDIX B – CHANGE CONTROL LOG

DATE	REVISION NUMBER	FIELD	CHANGE